



Dart Hawkesbury  
1270 Aberdeen St Hawkesbury, ON K6A 1K7 Canada  
Tel (613) 632-5200

# Purchasing Receipt

PO No	Supplier	Line Item No	Rel No	Terms	Purchased Item	Description	For Part No	Project	Equipment ID	Order Qty	Due Date	Received Quantity	Accounting Job No	Container No	Status	Receive Date	Price/Unit	Aging Days	Past Due	Total	Supplier Name
PO039984	MCM001-VU	2	1	2% 10 Net 30	8547K45	Tube ALT. P/N 8547K893				60	6/7/2018	48		S076790	Stock	5/31/2018	\$31.52 / ft	0		\$1,512.96	McMaster-Carr Supply Co.
										<b>Total:</b>										<b>\$1,512.96</b>	

Plex 5/31/2018 11:18 AM dart.Tollis Andrew



Dart Aerospace Ltd.  
1270 Aberdeen St  
Hawkesbury, ON  
K6A 1K7  
Canada

Tel (613) 632-5200

# **PURCHASE ORDER** **PO039984**

**Supplier:** MCM001-VU  
McMaster-Carr Supply Co,  
P.O. Box 7690  
Chicago, IL 60680-7690 USA  
Phone: 330 995 5500  
Fax: 330 995 9600

**PO No:** PO039984

**PO Date:** 5/24/18

**Due Date:** 5/29/18

**Purchase Order**

**Revision:**

**Revision Date:**

**Ship-To Contact:** Lavoie, Chantal  
clavoie@dartaero.com

**Ship To:** 1270 Aberdeen Street  
Hawkesbury  
ON  
K6A 1K7 Canada  
Phone: 613-632-5200

**Via:** Ground

**Pymt Terms:** 2% 10 Net 30

**Freight Terms:**

**Special Comments:**

MAY 24 2018

Items										
Line Item	Part	Supplier Part No	Description	Status	Due Date	Order Quantity	Received Quantity	Balance	Unit Price (USD)	Extended Price
1	MT-BRASS-C360-R1.500	2572T63 6 ft long	Brass C360 Round Bar 1.500"	Firmed	5/29/18	12 ft	0 ft	12 ft	\$46.55667/ft	\$558.68
2	8547K45	6 ft long	Tube ALT. P/N 8547K893 receive ea	Firmed	5/29/18	60 ft	0 ft	60 ft	\$34.25/ft	\$2,055.00
3	88805K74		6063 Aluminum 90° Angle, 1/8" Wall Thickness, 1/2" High x 1/2" Wide	Firmed	5/29/18	16 ft	0 ft	16 ft	\$1.36125/ft	\$21.78
4	1095K41	10/pk	Zerk	Firmed	5/29/18	10 Ea	0 Ea	10 Ea	\$0.352/Ea	\$3.52
5	95229A460	100/pk	Washer receive pcs	Firmed	5/29/18	100 pcs	0 pcs	100 pcs	\$0.0665/pcs	\$6.65
6	MDELINB0.750X3.000W	8739K45	M Delrin Bar, White : MATERIAL: DELRIN II 150E OR ACETRON GP ACETAL receive ft	Firmed	5/29/18	4 ft	0 ft	4 ft	\$24.16/ft	\$96.64
7	1897A59		Handle	Firmed	5/29/18	4 Ea	0 Ea	4 Ea	\$4.56/Ea	\$18.24
8	90107A029	100/pk	Flat Washer	Firmed	5/29/18	100 Ea	0 Ea	100 Ea	\$0.0825/Ea	\$8.25
9	90128A265	100/pk	Socket Head Cap Screw	Firmed	5/29/18	100 Ea	0 Ea	100 Ea	\$0.1322/Ea	\$13.22
10	9559K41	10/pk	O-Ring	Firmed	5/29/18	30 Ea	0 Ea	30 Ea	\$1.268/Ea	\$38.04
11	97524A032	100/pk	Sealing Blind Rivet receive ea	Firmed	5/29/18	200 Ea	0 Ea	200 Ea	\$0.0982/Ea	\$19.64
12	98002A202	10/pk	Binding Post	Firmed	5/29/18	10 Ea	0 Ea	10 Ea	\$0.415/Ea	\$4.15

Items										
Line Item	Part	Supplier Part No	Description	Status	Due Date	Order Quantity	Received Quantity	Balance	Unit Price (USD)	Extended Price
13	98380A473	10/pk	Dowel Pin	Firmed	5/29/18	20 Ea	25x 0 Ea	20 Ea	\$0.837/Ea	\$16.74
14	98381A510	50/pk	Pin	Firmed	5/29/18	50 Ea	50x 0 Ea	50 Ea	\$0.214/Ea	\$10.70
15	99908A102	50/pk	Flande Locknut, Steel	Firmed	5/29/18	50 Ea	50x 0 Ea	50 Ea	\$0.2526/Ea	\$12.63
16	C10-35	90576A118 50/pk	Cage Bumper Nut	Firmed	5/29/18	50 pcs	50x 0 pcs	50 pcs	\$0.1828/pcs	\$9.14
17	MT-O1-R0.750	8893K19 6 FT long	Tool Steel Round Bar 0.750 dia. receive ft	Firmed	5/29/18	18 ft	18x 0 ft	18 ft	\$5.98/ft	\$107.64
18	RBT18561-31	8485T13	10X Magna-Lite	Firmed	5/29/18	6 Ea	6x 0 Ea	6 Ea	\$26.29/Ea	\$157.74
19	D2484P	91343A100 10/pk	Lock Nut	Firmed	5/29/18	50 pcs	50x 0 pcs	50 pcs	\$0.363/pcs	\$18.15
20	12335A13	10 ft long	Edge Grip	Firmed	5/29/18	10 Ea	10x 0 Ea	10 Ea	\$2.43/Ea	\$24.30
21	8695K712		Polyurethane Rod 3/8 Dia., 48" Long, 80A (HARD)	Firmed	5/29/18	4 ft	4x 0 ft	4 ft	\$10.035/ft	\$40.14
Grand Total:									\$3,240.99	

## Order Notes

Procurement Quality Clauses  
A005 RIGHT OF ENTRY  
A016 PERSONNEL QUALIFICATION  
A026 CERTIFICATION OF MATERIAL CONFORMANCE  
A032 DOCUMENT SPECIAL REQUIREMENTS  
A033 STATEMENT OF CONFORMITY/TEST RECORDS FOR NAS, AN and MS FASTENERS  
A040 NOTIFICATION OF QUALITY ESCAPE  
A041 QUALITY MANAGEMENT SYSTEM  
A042 DART NOTIFICATION BY SUPPLIER  
A043 RETENTION OF QUALITY DOCUMENTS  
  
A048 COUNTERFEIT PARTS AVOIDANCE, DETECTION, MITIGATION AND DISPOSITION PROGRAM  
A049 SUPPLIER AWARENESS

Terms & Condition of Purchasing(Suppliers) and Procurement Quality Clauses are an integral part of our AS9100 requirements. To learn in detail, please visit [www.dartaerospace.com](http://www.dartaerospace.com) for further explanation.

Plex 5/24/18 2:48 PM dart.lavoie.chantal



200 Aurora Industrial Pkwy  
Aurora OH 44202-8087  
330-995-5500  
cle.sales@mcmaster.com

Dart Aerospace Ltd  
1270 Aberdeen St  
Hawkesbury ON K6A 1K7  
Canada

Purchase Order  
**PO039984**

Order Placed By  
**Chantal Lavoie**

McMaster-Carr Number  
**4088649-05**

Page 1 of 2

05/30/2018

Line	Product	Ordered	Shipped
2	<b>8547K893</b> Tube Made From PTFE, 1" OD x 1/2" ID	60 Feet	48

Shipped separately from our Cleveland warehouse on 05/24

3	<b>88805K74</b> Architectural 6063 Aluminum 90 Degree Angle, 1/8" Wall Thickness, 1/2" High x 1/2" Wide, 8 Feet Long	2 Each	2
4	<b>1095K41</b> Zinc-Plated Steel Grease Fitting, Straight, 1/4"-28 SAE-LT Male, 35/64" Overall Length	1 Pack	1
5	<b>95229A460</b> Cadmium-Plated Steel MIL. Spec. Washer for 5/16" Screw Size, NAS 1149-F0563P	1 Pack	1
6	<b>8739K45</b> White Delrin Acetal Resin Oversized Bar, 3/4" Thick, 3" Wide, 4' Length	4 Feet	4
7	<b>1897A59</b> Oval Grip Pull Handle with Threaded Holes, Aluminum, 4-9/16" Center-to-Center Width	4 Each	4
8	<b>90107A029</b> 316 Stainless Steel Washer for 1/4" Screw Size, 0.281" ID, 0.625" OD	1 Pack	1
9	<b>90128A265</b> Zinc-Plated Alloy Steel Socket Head Screw, M6 x 1 mm Thread, 25 mm Long	1 Pack	1
10	<b>9559K41</b> Ultra-Chemical-Resistant Rigid PTFE O-Ring, 1/8 Fractional Width, Dash Number 219	3 Packs	3
11	<b>97524A032</b> Sealing Blind Rivets, Aluminum, Domed Head, with Aluminum Mandrel, 1/8" Diameter, 0.425" Long	2 Packs	2
12	<b>98002A202</b> Steel Binding Barrels and Screws, 10-24 Thread Size, for 3/8"-1/2" Material Thickness	1 Pack	1
13	<b>98380A473</b> 416 Stainless Steel Dowel Pins, 1/8" Diameter, 3/4" Long	1 Pack	1
14	<b>98381A510</b> Dowel Pin, Alloy Steel, 3/16" Diameter, 1" Long	1 Pack	1

# Packing List

200 Aurora Industrial Pkwy  
Aurora OH 44202-8087  
330-995-5500  
cle.sales@mcmaster.com

Dart Aerospace Ltd  
1270 Aberdeen St  
Hawkesbury ON K6A 1K7  
Canada

Purchase Order  
**PO039984**

Order Placed By  
**Chantal Lavoie**

McMaster-Carr Number  
**4088649-05**

Page 2 of 2

05/30/2018

Line	Description	Ordered	Shipped
15	<b>99908A102</b> High-Strength Steel Nylon-Insert Flange Locknut, Class 10, Zinc Yellow-Chromate Plated, M8 x 1.25 mm Thread	1 Pack	1
16	<b>90576A118</b> Medium-Strength Steel Nylon-Insert Locknut, Class 8, Zinc-Plated, M10 x 1.5 mm Thread	1 Pack	1
17	<b>8893K19</b> Tight-Tolerance Multipurpose O1 Tool Steel Rod, 0.7500" Diameter, 6 Feet Long	3 Each	3
18	<b>8485T13</b> Incandescent-Illuminated Magnifying Glass, 10x, 1-1/4" Long x 1-3/8" Wide Lens	6 Each	6
19	<b>91343A100</b> 316 Stainless Steel Serrated Flange Locknut, Super-Corrosion-Resistant, 1/4"-20 Thread Size	5 Packs	5
20	<b>12335A13</b> Water- & Weather-Resistant Rubber Push-on Seal with Bulb on Top, Hollow, for 3/64"-1/16" Edge, 10' Long	10 Feet	10
21	<b>8695K712</b> Abrasion-Resistant Polyurethane Rubber Rod, 48" Long, 3/8" Diameter, 80A Durometer	1 Each	1
1	<b>2572T63</b> Ultra-Machinable 360 Brass Rod with Certification, 1-1/2" Diameter, 6 Feet Long	2 Each	2

## Expected to ship

2	<b>8547K893</b> Tube Made From PTFE, 1" OD X 1/2" ID	60 Feet	12 May 31-Jun 7
---	--	------------	-----------------

# MATERIAL RECEIPT INSPECTION FORM

MATERIAL: 8547K45 (8547K893)  
 DATE: MAY 3 1 2018

PO / BATCH NO.: 039984/5076790

MATERIAL CERT REC'D: Yes  
 QUANTITY RECEIVED: 481  
 QUANTITY INSPECTED: 481  
 QUANTITY REJECTED: 0

THICKNESS ORDERED: 1.000  
 THICKNESS RECEIVED: 1.000  
 SHEET SIZE ORDERED: N/A  
 SHEET SIZE RECEIVED: N/A

DESCRIPTION	NCR (Check Y/N)	COMMENTS
SURFACE DAMAGE	Y <input checked="" type="radio"/> N <input type="radio"/>	
CORRECT FINISH	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	
CORROSION	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	
CORRECT GRAIN DIRECTION	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	
CORRECT MATERIAL PER M-DRAWING	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	Part # 8547K45
CORRECT THICKNESS	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	
PHOTO REQUIRED	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	
CORRECT REF # TO LINK CERT	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	PO # 039984
CORRECT MATERIAL IDENTIFICATION	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	
CORRECT M# ON THE MATERIAL	<input checked="" type="radio"/> Y <input type="radio"/> N <input type="radio"/>	
DOES THIS MATERIAL REQUIRE ENGINEERING SIGN OFF	Y <input type="radio"/> N <input checked="" type="radio"/>	
DOES THIS REQUIRE AN EXTRUSION REPORT	Y <input type="radio"/> N <input checked="" type="radio"/>	

CUT SAMPLE PIECE OF MATERIAL AND PREFORM A HARDNESS CHECK. RECORD RESULTS BELOW					
	HRC	HRB	DUR A	DUR D	WEBSTER
TYPE OF MATERIAL					
SIZE OF TEST SAMPLE					
HARDNESS / DUROMETER READING					

*testers located in the Quality Office*

QC 18 INSPECTION	ENGINEERING SIGNOFF (if required)
INSPECTED BY: <u>DAS 11</u>	SIGNED OFF BY: _____
DATE: <u>9-89 MAY 3 1 2018</u>	DATE: _____

Attach this inspection sheet with the corresponding material cert and remit to be scanned and received in

## Teflon® PTFE

For comparative information about plastics, see page 3692.

### Tubes Made from Teflon® PTFE



- Color: White
- Temperature Range: -350° to 500° F
- Tensile Strength: 4,500 psi (Poor)
- Impact Strength: 2.00 ft.-lbs./in. (Good)
- For Use Outdoors: Yes
- Specifications Met: ASTM D1710, Made of FDA Listed Material, UL 94V0

Protect wires, cords, and anything that can fit inside these tubes from solvents. They're also used to fabricate parts that slide and roll, such as bearings and gears. These tubes are made from virgin Teflon® PTFE, which surpasses most plastics when it comes to chemical resistance and performance in extreme temperatures. It is also an excellent electrical insulator. OD is oversized and ID is undersized for finishing to the sizes listed.

OD	Tolerance Rating	ID	Wall Thick.	Lengths, ft.	Per Ft.
1/4"	Oversized	1/16"	3/32"	1, 2, 3, 4, 5, 6	8547K22 \$4.76
1/4"	Oversized	1/8"	1/16"	1, 2, 3, 4, 5, 6	8547K23 3.26
1/4"	Oversized	3/16"	1/16"	1, 2, 3, 4, 5, 6	8547K24 4.47
3/8"	Oversized	1/4"	1/16"	1, 2, 3, 4, 5, 6	8547K11 4.89
7/16"	Oversized	5/16"	1/16"	1, 2, 3, 4, 5, 6	8547K25 6.68
1/2"	Oversized	1/4"	1/8"	1, 2, 3, 4, 5, 6	8547K31 8.68
1/2"	Oversized	5/16"	3/32"	1, 2, 3, 4, 5, 6	8547K62 7.89
1/2"	Oversized	3/8"	1/16"	1, 2, 3, 4, 5, 6	8547K12 6.90
5/8"	Oversized	7/16"	1/16"	1, 2, 3, 4, 5, 6	8547K27 7.36
5/8"	Oversized	1/4"	3/16"	1, 2, 3, 4, 5, 6	8547K32 14.62
5/8"	Oversized	3/8"	1/8"	1, 2, 3, 4, 5, 6	8547K26 12.00
3/4"	Oversized	1/2"	1/16"	1, 2, 3, 4, 5, 6	8547K61 7.60
3/4"	Oversized	1/4"	1/4"	1, 2, 3, 4, 5, 6	8547K42 24.19
3/4"	Oversized	3/8"	3/16"	1, 2, 3, 4, 5, 6	8547K63 19.15
3/4"	Oversized	1/2"	1/8"	1, 2, 3, 4, 5, 6	8547K13 14.49
3/4"	Oversized	5/8"	1/16"	1, 2, 3, 4, 5, 6	8547K28 8.86
7/8"	Oversized	3/8"	1/4"	1, 2, 3, 4, 5, 6	8547K44 36.54
7/8"	Oversized	5/8"	1/8"	1, 2, 3, 4, 5, 6	8547K14 17.41
1"	Oversized	1/2"	1/4"	1, 2, 3, 4, 5, 6	8547K45 34.25
1"	Oversized	5/8"	3/16"	1, 2, 3, 4, 5, 6	8547K46 30.67
1"	Oversized	3/4"	1/8"	1, 2, 3, 4, 5, 6	8547K15 20.15
1"	Oversized	7/8"	1/16"	1, 2, 3, 4, 5, 6	8547K29 13.92
1 1/4"	Oversized	7/8"	3/16"	1, 2, 3, 4, 5, 6	8547K16 32.13
1 1/4"	Oversized	1"	1/8"	1, 2, 3, 4, 5, 6	8547K47 25.63
1 3/8"	Oversized	7/8"	1/4"	1, 2, 3, 4, 5, 6	8547K39 41.30
1 3/8"	Oversized	1"	3/16"	1, 2, 3, 4, 5, 6	8547K17 34.67
1 1/2"	Oversized	1"	1/4"	1, 2, 3, 4, 5, 6	8547K35 45.95
1 1/2"	Oversized	1 1/4"	1/8"	1, 2, 3, 4, 5, 6	8547K18 26.57
1 3/4"	Oversized	1 3/8"	3/16"	1, 2, 3, 4, 5, 6	8547K19 43.25
1 3/4"	Oversized	1 1/2"	1/8"	1, 2, 3, 4, 5, 6	8547K38 31.02
1 7/8"	Oversized	1 1/2"	3/16"	1, 2, 3, 4, 5, 6	8547K36 46.27
2"	Oversized	1 1/2"	1/4"	1, 2, 3, 4, 5, 6	8547K21 59.58
2"	Oversized	1 3/4"	1/8"	1, 2, 3, 4, 5, 6	8547K41 35.87
2 1/4"	Oversized	1 1/2"	3/8"	1, 2, 3, 4, 5, 6	8547K33 96.83
2 1/2"	Oversized	2"	1/4"	1, 2, 3, 4, 5, 6	8547K37 78.10
3"	Oversized	2"	1/2"	1, 2, 3, 4, 5, 6	8547K34 148.71

3" Lg. 6" Lg. 12" Lg.

OD	Tolerance Rating	ID	Wall Thick.	Each	Each	Each
3 1/2"	Oversized	3"	1/4"	8556K12 \$59.35	8556K15 \$98.75	8556K18 \$165.40
4"	Oversized	2"	1"	8556K14 96.60	8556K17 168.62	8556K19 314.37
4"	Oversized	2 1/2"	3/4"	8556K11 81.91	8556K41 144.90	8556K71 255.42
4"	Oversized	3"	1/2"	8556K16 62.91	8556K46 108.20	8556K76 196.73
4"	Oversized	3 1/2"	1/4"	8556K22 66.19	8556K24 105.68	8556K25 177.49
4 1/2"	Oversized	4"	1/4"	8556K26 70.70	8556K28 118.20	8556K29 195.30
5"	Oversized	2 1/2"	1 1/4"	8556K13 139.33	8556K43 254.23	8556K73 475.10
5"	Oversized	4"	1 1/2"	8556K27 75.61	8556K57 138.37	8556K87 244.05
6"	Oversized	3"	1 1/2"	8556K21 189.09	8556K51 353.66	8556K91 642.05
6"	Oversized	4"	1"	8556K23 148.62	8556K53 271.18	8556K83 498.60
7"	Oversized	5"	1 1/2"	8556K33 92.41	8556K63 160.40	8556K93 288.17
7"	Oversized	3"	2"	8556K36 271.18	8556K66 506.77	8556K96 936.76
7"	Oversized	5"	1"	8556K37 174.96	8556K67 325.40	8556K97 579.62
7"	Oversized	5 1/2"	3/4"	8556K38 142.06	8556K68 258.77	8556K98 467.44

### Rods Made from Teflon® PTFE



- Color: White
- Temperature Range: -350° to 500° F
- Tensile Strength: 4,500 psi (Poor)
- Impact Strength: 2.00 ft.-lbs./in. (Good)
- For Use Outdoors: Yes
- Specifications Met: 3-A Certified, ASTM D1710, Made of FDA Listed Material, UL 94V0

Fabricate parts that slide and roll, such as bearings, gears, and rollers. Teflon® PTFE, which surpasses most plastics when it comes to chemical resistance in extreme temperatures. It resists most solvents and is an excellent electrical

Dia.	Dia. Tolerance	Lengths, ft.	Per Ft.
1/8"	0" to +0.002"	1, 2, 3, 4, 5, 6	8546K31 \$1.21
3/16"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K32 1.61
1/4"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K11 2.21
5/16"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K35 3.61
3/8"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K12 5.11
7/16"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K42 5.61
1/2"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K13 7.31
9/16"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K43 9.01
5/8"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K14 10.91
11/16"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K44 12.91
3/4"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K15 15.41
13/16"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K45 16.11
7/8"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K25 21.11
15/16"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K46 24.01
1"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K16 27.11
1 1/8"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K36 34.71
1 1/4"	0" to +0.005"	1, 2, 3, 4, 5, 6	8546K17 40.81
1 3/8"	0" to +0.083"	1, 2, 3, 4, 5, 6	8546K27 46.01
1 1/2"	0" to +0.090"	1, 2, 3, 4, 5, 6	8546K18 53.11
1 5/8"	0" to +0.098"	1, 2, 3, 4, 5, 6	8546K28 64.31
1 3/4"	0" to +0.105"	1, 2, 3, 4, 5, 6	8546K29 77.81
1 7/8"	0" to +0.113"	1, 2, 3, 4, 5, 6	8546K41 85.81
2"	0" to +0.120"	1, 2, 3, 4, 5, 6	8546K19 96.71
2 1/4"	0" to +0.135"	1, 2, 3, 4, 5, 6	8546K47 115.11
2 1/2"	0" to +0.150"	1, 2, 3, 4, 5, 6	8546K21 158.31
2 3/4"	0" to +0.165"	1, 2, 3, 4, 5, 6	8546K48 176.71
3"	0" to +0.180"	1, 2, 3, 4, 5, 6	8546K22 221.71
3 1/4"	0" to +0.195"	1, 2, 3, 4, 5, 6	8546K49 246.81
3 1/2"	0" to +0.210"	1, 2, 3, 4, 5, 6	8546K23 299.11
4"	0" to +0.240"	1, 2, 3, 4, 5, 6	8546K24 358.81
4 1/2"	0" to +0.270"	1, 2, 3, 4, 5, 6	8546K51 405.41
5"	0" to +0.300"	1, 2, 3, 4, 5, 6	8546K34 497.71
6"	0" to +0.360"	1, 2, 3, 4, 5, 6	8546K52 672.91

Dia.	Dia. Tolerance	1" Lg.	3" Lg.	6" Lg.
2"	0" to +0.120"	1396T11 \$12.40	1396T21 \$31.88	1396T31 \$
3"	0" to +0.180"	1396T12 28.05	1396T22 72.15	1396T32 1
4"	0" to +0.240"	1396T13 49.84	1396T23 129.16	1396T33 2
5"	0" to +0.300"	1396T14 68.68	1396T24 180.29	1396T34 2
6"	0" to +0.360"	1396T15 96.14	1396T25 252.36	1396T35 4
8"	0" to +0.157"	1396T16 190.94	1396T26 627.39	1396T36 1.0

### Hexagonal Bars Made from Teflon® PTFE



- Color: White
- Temperature Range: -350° to 500° F
- Tensile Strength: 4,500 psi (Poor)
- Impact Strength: 2.00 ft.-lbs./in. (Good)
- For Use Outdoors: Yes
- Specifications Met: ASTM 4894, ASTM D1710, Made of FDA Listed Material, UL 94V0

Use these hexagon bars to fabricate parts that slide. They're made from virgin most plastics when it comes to chemical resistance and performance in solvents and is an excellent electrical insulator.

Wd.	Wd. Tolerance	Lengths, ft.	Per Ft.
1/4"	0" to +0.01"	1, 2, 3, 4, 5, 6	8544K11 \$2.85
3/8"	0" to +0.01"	1, 2, 3, 4, 5, 6	8544K13 16.55